

Package ‘aLBI’

November 13, 2024

Type Package

Title Estimating Length-Based Indicators for Fish Stock

Version 0.1.6

Maintainer Ataher Ali <ataher.cu.ms@gmail.com>

Description Provides tools for estimating length-based indicators from length frequency data to assess fish stock status and manage fisheries sustainably. Implements methods from Cope and Punt (2009) <doi:10.1577/C08-025.1> for data-limited stock assessment and Froese (2004) <doi:10.1111/j.1467-2979.2004.00144.x> for detecting overfishing using simple indicators. Key functions include:
FrequencyTable(): Calculate the frequency table from the collected and also the extract the length frequency data from the frequency table with the upper length_range. A numeric value specifying the bin width for class intervals. If not provided, the bin width is automatically calculated using Sturges (1926) <doi:10.1080/01621459.1926.10502161> formula.
CalPar(): Calculates various lengths used in fish stock assessment as biological length indicators such as asymptotic length (Linf), maximum length (Lmax), length at sexual maturity (Lm), and optimal length (Lopt).
FishPar(): Calculates length-based indicators (LBIs) proposed by Froese (2004) <doi:10.1111/j.1467-2979.2004.00144.x> such as the percentage of mature fish (Pmat), percentage of optimal length fish (Popt), percentage of mega spawners (Pmega), and the sum of these as Pobj. This function also estimates confidence intervals for different lengths, visualizes length frequency distributions, and provides data frames containing calculated values.
FishSS(): Makes decisions based on input from Cope and Punt (2009) <doi:10.1577/C08-025.1> and parameters calculated by FishPar() (e.g., Pobj, Pmat, Popt, LM_ratio) to determine stock status as target spawning biomass (TSB40) and limit spawning biomass (LSB25). These tools support fisheries management decisions by providing robust, data-driven insights.

Depends R (>= 3.5.0)

Imports dplyr

Suggests testthat, knitr, rmarkdown, devtools, readxl

License GPL-3

Encoding UTF-8

LazyData true

URL <https://github.com/Ataher76/aLBI>

BugReports <https://github.com/Ataher76/aLBI/issues>

RoxygenNote 7.3.1

VignetteBuilder knitr

NeedsCompilation no

Author Ataher Ali [aut, cre],
Mohammed Shahidul Alam [aut]

Repository CRAN

Date/Publication 2024-11-13 17:30:02 UTC

Contents

CPdata	2
ExData	3
FishPar	4
FishSS	4
FrequencyTable	5
lenfreq01	6
lenfreq02	7
Index	8

CPdata

CPdata: Example dataset for aLBI package

Description

This dataset contains description of CPdata.

Usage

```
data(CPdata)
```

Format

A data frame with [number of rows] rows and 11 columns:

A [description of column A]

B [description of column B]

C [description of column C]

D [description of column D]

E [description of column E]

F [description of column F]

G [description of column G]
H [description of column H]
I [description of column I]
J [description of column J]
Tx [description of column Tx]

Source

[Include the source of the data if available]

Examples

```
data(CPdata)  
head(CPdata)
```

ExData

ExData: Example raw length dataset for aLBI package

Description

This dataset contains description of ExData.

Usage

```
data(ExData)
```

Format

A data frame with [number of rows] rows and 1 columns:

Length [description of column Length measured]

Source

[Include the source of the data if available]

Examples

```
data(ExData)  
head(ExData)
```

FishPar	<i>Calculate Length-Based Indicators for Fish Stock Assessment #'@importFrom graphics abline axis barplot box boxplot hist legend lines par rect segments text</i>
---------	--

Description

This function calculates various length-based indicators for fish stock assessment using length frequency data and bootstrap resampling.

Usage

```
FishPar(data, resample, progress)
```

Arguments

data	A data frame containing two columns: Length and Frequency.
resample	An integer indicating the number of bootstrap resamples.
progress	A logical value indicating whether to display progress.

Value

A list containing estimated length parameters, Froese indicators, and other relevant metrics.

Examples

```
data <- data.frame(Length = c(10, 20, 30, 40, 50), Frequency = c(5, 10, 15, 20, 25))
FishPar(lenfreq01, 100, progress = FALSE)
utils::data("lenfreq01", package = "aLBI")
utils::data("lenfreq02", package = "aLBI")
```

FishSS	<i>Assess Stock Status Based on Calculated Parameters</i>
--------	---

Description

This function assesses the stock status based on parameters calculated by the FishPar function.

Usage

```
FishSS(data, LM_ratio, Pobj, Pmat, Popt)
```

Arguments

data	A data frame containing the necessary columns for stock status calculation.
LM_ratio	A numeric value representing the length at maturity ratio.
Pobj	A numeric value representing the percentage objective.
Pmat	A numeric value representing the percentage of mature fish.
Popt	A numeric value representing the percentage of optimally sized fish.

Value

A numeric vector containing TSB40 and LSB25.

Examples

```
utils::data("CPdata", package = "aLBI")
FishSS(CPdata, 0.75, 100, 30, 25)
```

FrequencyTable	<i>Generate a Frequency Distribution Table for Fish Length Data</i>
----------------	---

Description

This function creates a frequency distribution table for fish length data, allowing users to specify or calculate the ideal bin width based on Sturges' formula. The function returns a data frame containing the upper boundary of each length class and its associated frequency.

Arguments

data	A numeric vector or data frame containing fish length measurements. If a data frame is provided, the first numeric column will be selected.
bin_width	(Optional) A numeric value specifying the bin width for class intervals. If not provided, the bin width is automatically calculated using Sturges' (1926) formula.

Details

The ideal bin width is calculated if not provided, based on Sturges' formula:

$$\text{Bin Width} = \frac{\text{Range}}{\text{Number of Classes}}$$

where the number of classes is determined as $1 + 3.322 \log_{10}(N)$ for a dataset of size N .

Value

A data frame with two columns: Upper_Length representing the upper boundary of each length class, and Frequency representing the count of observations within each class.

Examples

```
# Generate random fish length data
set.seed(123)
fish_lengths <- data.frame(Length = runif(2000, min = 5, max = 70))

# Create a frequency table with an automatically calculated bin width
FrequencyTable(data = fish_lengths$Length)

# Specify a bin width of 5 and generate a frequency table
FrequencyTable(data = fish_lengths$Length, bin_width = 5)
utils::data("ExData", package = "aLBI")
```

lenfreq01

lenfreq01: Example dataset for aLBI package

Description

This dataset contains description of lenfreq01.

Usage

```
data(lenfreq01)
```

Format

A data frame with [number of rows] rows and 2 columns:

Frequency [description of column Frequency]

Length [description of column Length]

Source

[Include the source of the data if available]

Examples

```
data(lenfreq01)
head(lenfreq01)
```

`lenfreq02`*lenfreq02: Example dataset for aLBI package*

Description

This dataset contains description of lenfreq02.

Usage

```
data(lenfreq02)
```

Format

A data frame with [number of rows] rows and 2 columns:

Frequency [description of column Frequency]

LengthClass [description of column LengthClass]

Source

[Include the source of the data if available]

Examples

```
data(lenfreq02)
head(lenfreq02)
```

Index

CPdata, [2](#)

ExData, [3](#)

FishPar, [4](#)

FishSS, [4](#)

FrequencyTable, [5](#)

lenfreq01, [6](#)

lenfreq02, [7](#)